

HBQ-068 双头绞线机

产品简介

HBQ-068 双头绞线机主要应用于线束加工领域,可对线束进行双绞线绞合处理。双工位可以交替连续工作,一边装夹,一边进行绞合,节省时间。也可以不交替操作使用。

产品特征

- 高效:**双工位可交替连续工作，一工位装夹,一工位进行绞合转速最高达3000r/min
- 安全:**前后端防护罩全防护设计
- 扩展:**支持 MES 联网

产品参数

型号	HBQ-068
线径范围	0.13~4mm²
绞线长度	150~8000mm（可定制）
绞线速度	3000r/min（最大）
开口长度	30~100mm
绞线数量	2/3pcs
节距精度	±10%
气源	0.5~0.6MPa

电源	AC220V
功率	500W（交替模式） 900W（单动模式）
尺寸	L3300×W650×H1400mm（L 定制）

HBQ-068 Twisting Machine

INTRODUCTION

HBQ-068 is mainly used in the field of wire harness processing and double wire twisting. The two work stations of HBQ-068 work alternatively, so the operators can clamp wires on one workstation while the other one is perform twisting and this increases the production efficiency. Two work station could work alternatively or separately.

FEATURES

●High efficiency

Double workstations can work continuously and alternately, clamping and twisting aimultaneously;

The speed is up to 3000r/min;

●Safe

Full protection design of safety cover for front and rear;

●Extension

Support MES networking;

SPECIFICATIONS

Type	HBQ-068
Wire Cross Sections	0.13~4mm ²
Twisting Length	150-8000mm (customizable)
Twisting Speed	3000r/min (max)
Untwisted Length	30-100mm
Twisting Number	2/3pcs
Pitch Accuracy	±10%
Power Supply	220V
Air Supply	0.5-0.6Mpa
Power	500W (Altemate Mode) 900W (Single Action Mode)
Dimension	L3300×W650×H1400mm ("L"customizable)